

轻量沟形钢

寸法 A x B x C	肉厚 t	重量		
		kg/m	kg/6m	kg/8m
40x20	1.6	0.939	5.63	
	2.3	1.31	7.86	
40x40	3.2	2.75	16.5	
60x30	1.6	1.44	8.64	
	2.3	2.03	12.2	
80x40	2.3	2.75	16.5	
100x40	2.3	3.11	18.7	
	3.2	4.26	25.6	
100x50	2.3	3.47	20.8	
	3.2	4.76	28.6	38.1
120x40	3.2	4.76	28.6	38.1
150x50	3.2	6.02	36.1	48.2
	4.5	8.31	49.9	66.5
150x75	4.5	10.1	60.6	80.8
200x50	3.2	7.27	43.6	58.2
	4.0	9.0	54.0	72.0
	4.5	10.1	60.6	80.8
200x75	4.5	11.8	70.8	94.4
	6.0	15.6	93.6	125
250x50	4.0	10.6	63.6	84.8
	4.5	11.8	70.8	94.4
250x75	4.5	13.6	81.6	109
	6.0	17.9	107	143
300x50	4.0	12.1	72.6	96.8
	4.5	13.6	81.6	109
350x50	4.5	15.4	92.4	123
400x75	4.5	18.9	113	151
	6.0	25.0	150	200
450x75	4.5	20.7	124	166
	6.0	27.3	164	218